


INDUSTRIAL SAFETY CAP - PEAKED BRIM



COMPLIANCE

- SABS Mark certification: 4886/12692
- SANS 1397:2003 standard compliant
- Department of Minerals and Energy GME Approved
HH 2006-03-07
HH 2006-03-08
- 440 VAC insulated
- Proudly made in South Africa

PACKAGING

- Standard harness:
20 assembled per clear bag 75cm x 55cm x 24cm x 5.8kg
40 assembled per woven export bag 140cm x 55cm x 24cm x 11.6kg
- Plastic ratchet harness:
10 assembled per clear bag 56cm x 55cm x 24cm x 3kg
30 assembled per woven export bag 168cm x 55cm x 24cm x 9.8kg
- Webbing ratchet harness:
10 assembled per clear bag 56cm x 55cm x 24cm x 3kg
30 assembled per woven export bag 168cm x 55cm x 24cm x 9kg

INSTRUCTIONS

To provide protection the helmet must be fitted correctly and harness adjusted to the size of the users head. One size fits all, adjustable headband 50cm-64cm. Storage must be provided in a cool clean environment away from harmful ultra-violet light exposure. Do not stack more than 6 rows horizontally on top of each other. Do not stack any objects on top. Packaging for bulk handling should be in clear PE bags, woven bags or boxes. Date of issue must be recorded on this label in the space provided. Recommended shelf life: 24 months. Recommended period of use from date of issue: 12 months. Or as otherwise considered necessary by safety officer, representative or specified requirements.

WARNING

This helmet provides limited protection to the upper head against falling objects and impacts and is designed to absorb the energy of an impact by partial destruction or damage to shell, harness and/or both. Although damage may not be apparent, helmets subjected to an impact should be replaced immediately. Components of the helmet should not be removed/modified/adapted to a purpose or to fit attachments in any way. Inspect and maintain the helmet and harness on a regular basis. Replace damaged or worn harness immediately. Only use SAFECO replacement harness. Application of solvents, aerosols, paint, petroleum products and/or cleaning agents may cause damage to the helmet. Only use a solution of mild soapy water to clean the helmet.

COLOURS



PRODUCT DESCRIPTION

- Safeco industrial safety cap
- Peaked brim
- 6 Point suspension harness
- 3 harness options: standard, ratchet plastic & ratchet webbing
- SABS SANS 1397 compliant
- 17 Standard colours

TECHNICAL SPECIFICATIONS

- High impact resistant shell.
- Assembled weight: Standard harness 284g, plastic ratchet harness 306g, webbing ratchet harness 300g
- One size fits all
- 6 Point suspension harness attachment
- Harness nape strap adjustment from 50cm to 64cm. Available in the following:
 - a. 6 pin buckle fastener
 - b. Auto-locking ratchet
 - c. Auto-locking ratchet and webbing
- 40mm Peaked brim
- 270° Gutter
- 2 Accessory slots
- 3 Lugs for chinstraps
- 2 Year UV stabilised shell
- Materials: Poly Propylene (PP) Shell, Poly Ethylene (LLDPE) 2-part harness, Tricot foam cushion sweatband
- Shell colours: White, Royal Blue, Yellow, Orange, Red, Green, Lime, Grey, Sasol Blue, Bright Pink, Hi Viz Lemon, Sun Yellow, Maroon, Brown, Purple, Navy and Black
- Harness colour: Natural
- Sweatband colour: Black